



LinxSeries[®]CJ400

Continuous InkJet Printing

Inkjet Technology by

L I N X







Technology by

Inkie

L I N X



Features and Benefits:



Dimensions:

- Easi-Change® service module offers up to 6,000 hours between scheduled maintenance.
- Compact lightweight design under 30 lbs., the CJ400 is the lightest printer on the market.
- Color touch screen with on-screen help provides easy to follow step by step message creation and editing without manuals.
- 4 line settings can be saved for up to 4 production lines to allow quick change over for multiple production line applications.
- USB message and printer back up allows for sharing messages and settings between printers. Download bitmap logos to the printer via USB for custom printing.
- Auto-flush printhead cleaning performs a flush cleaning of the printhead and lines on startup and shutdown of the CJ400.
- SureFill® fluid replenishment ensures fast, mistake proof refills while printing ensures maximum uptime.
- 62 micron printhead nozzle provides savings up to 40% on ink usage compared to other CIJ printers.
- Large message storage provides the capacity to store up to 1,000 messages.

450 mm

Top Elevatio

323 mm

Front Elevation

Printer Specifications:

i inition oppoontoutiono.		00111001101107
Printhead with 2M Conduit, Standard Printhead/Conduit Options Max Lines of Print Character Height Range	MK9 No 2 Standard, 3 Optional 0.07" to 0.34" Standard, Optional 0.78" Carton Coding Message Type	Touch Screen Logojet PC Based Me and Logo Creatior and DDE Driver So RS232 Port
Max Speed; Single Line Print	511 fpm	Ethernet Option
Ink Range	Dye Based	Parallel I/O Option
Automatic Date Codes,		USB Port for Messag
Sequential Numbering	Yes	Setting Back Up a
Timed Messages	Yes	Shaft Encoder, Produ
Graphics/Logo Printing	Yes	External Single St
Barcodes, Common		Volt-Free Contact
Linear & 2D Datamatrix	No	
Memory Capacity (# of Messages)	1,000	
Ingress Protection Rating	IP53 Resists Liquid Splashes from Angles up to 60° from Vertical	
Base and Enclosure	Stainless Steel and Chemical Resistant PTB Polymer	
Operating Temperature Range	41-113°F	
Humidity Range (r.h., Non-Condensing) 90% Max	
Power Supply	100-230V 50/60 Hz	
Power Consumption	50W	

29.7 lbs

Connections / Interfacing Specifications:

323 mm (including clearance at back of printer)

Touch Screen Logojet PC Based Message	Yes
and Logo Creation Software	
and DDE Driver Software	No
RS232 Port	Yes
Ethernet Option	Yes
Parallel I/O Option	No
USB Port for Message and Printer	
Setting Back Up and Restore	Yes
Shaft Encoder, Product Detector,	
External Single Stage Alarm,	
Volt-Free Contact Alarm Connection	I Yes

Side Elevation

Ē

364

Distributor Information:

Weight

Regulatory Approvals



Delaware Valley Packaging Group is an authorized full servicing distributor of the complete line of FoxJet systems.

1425 Wells Drive Bensalem, PA 19020 800-727-6566

TÜV/NRTL, CE Mark, RoHS, FCC, GOST-R



1 Missouri Research Park Drive • St. Charles, MO 63304 Ph: 800.369.5384 • www.foxjet.com • email@foxjet.com www.foxjet.com youtube.com/itwfoxjet