## LITTLE DAVID



# CASE SEALER LD-195B



### LOW PROFILE/NARROW - UNIFORM CASE SEALING

The Little David \* LD-19SB is the latest in a series of industrial grade, high performance case sealers from Little David \*.

This case sealer is designed to seal low profile and narrow case sizes and is unrivaled in its sheer efficiency, easy-of-maintenance, and durability.



#### **PERFORMANCE & DESIGN FEATURES:**

HEAVY DUTY CONSTRUCTION
Engineered and assembled in South Canaan, PA
under the highest quality standards. The Little
David brand is committed to your satisfaction.

SIMPLE AND RELIABLE OPERATION Push button start controls, e-stop and single mast design ensures safety for the operator.

#### VERSATILE

Top and bottom tape cartridges are removable and interchangable. Capable of processing a case as low as 2.5" and as narrow as 3.25".

QUICK/EASY CHANGEOVER Slide and lock adjustment for case height and turn handle to adjust for case width.

<sup>\*</sup>Shown with optional infeed pack table.

## LITTLE DAVID © LD-19SB

The Little David \* LD-19SB is a semi-automatic case sealer designed for processing low profile and/or narrow case sizes. The LD-19SB needs 2 adjustments for the height and width of the case befre presented to it by an operator. The adjustments are fixed in place to process a series of uniform or same size cases. Cases are top and bottom sealed with 2" or 3" tape.

#### LITTLE DAVID \* PERFORMANCE & DESIGN FEATURES:

- Side belt case sealer with single mast design is safe and easy to operate
- Processes low profile and or narrow cases
- Slide and lock adjustment for height and turn handle to adjust for width.
- Interchangeable cartridges (top and bottom)

#### **OPTIONS OF THE LD-19SB:**

- Casters
- Flat Exit Pack Table
- Roller Exit Pack Table
- Leg Extensions
- Mirror Image
- Nema 12 Electrical Package
- 3 Phase Motor
- Infeed Pack Table

#### **SPECIFICATIONS:**

Power Requirements: 110 volts, 60 cycle, single phase

Air Requirements:

None

Operating Speed: Continuous belt drive; 72' per minute (21.95 m/min).

Closure Material: Pressure Sensitive Tape

Weight: 475 lbs. (215 kg.), uncrated

#### CASE CAPACITY:

Length: 5" - infinite Width: 3" - 20" Height: 2-1/2" - 24"

#### **MACHINE DIMENSIONS:**

50" (127cm) high 39" (99.06cm) long 57-1/4" (145.42cm) wide



DISTRIBUTED BY:

#### **LOVESHAW**

2206 East Turnpike P.O. Box 83, South Canaan, PA 18459 Tel: (570) 937-4921 Fax: (570) 937-3229 Toll Free: (800) 572-3434

#### **LOVESHAW Europe**

Unit 9 Brunel Gate West Portway Industrial Estate Andover, Hampshire, England SP10 3SL Tel: (1264) 357511 Fax: (1264) 355963

