III PROMACH





The affordable way to lower your wrapping cost and get consistently wrapped loads

The Sentry by Orion is an entry level, semi-automatic turntable style stretch wrapping machine for economical and efficient unitization of pallet loads with stretch film. The Sentry can dramatically increase efficiency and lower film cost per load, especially compared to manually applying stretch film by hand. The affordable Sentry unitizes pallet loads quickly and efficiently using the least amount of stretch film for a wrapped load that looks great and arrives at its destination the same way you shipped it. All AC motors, durable steel construction, and proven components assure a long and reliable service life.

FEATURES AND BENEFITS

- Wraps pallet loads (52" x 52" x 80"H max.) weighing up to 4,000 pounds with a variable speed 65" turntable running at a maximum of 9 RPM
- 200% Powered prestretch with variable speed and adjustable film tension
- Rugged steel construction, forklift portable
- · Automatic load height sensing photoeye
- Adjustable/separate top & bottom wrap counter
- Heavy-duty industrial chain drives the carriage and the turntable
- Home position alignment stops turntable in same position after each cycle
- User-friendly multi-language controller

EoL





Sentry by Orion SEMI AUTOMATIC STRETCH WRAPPER

MACHINE SPECIFICATIONS

Rotation Speed: Variable to 9 RPM

Max. Load Size: 52" x 52" x 80" H (95" Option)

Max. Load Weight: 4,000 lbs.

Film Prestretch: 200%

Film Tension Control: Adjustable


Electrical: 120VAC, 60 cycle, 1-phase, 15 amps


Machine Weight: 1,650 lbs.

Warranty: 2 Years

OPTIONS AND ACCESSORIES

- · Extended Mast
- Pallet Jack Ramp
- · Electric Walkie Ramp







FEATURES



Loading film is fast and easy: open the hinged door, pull the film tail through, and close the door. Power is disconnected when the door is opened.



The control panel features a user-friendly display and knobs for turntable speed, carriage speed and film tension.



Structural steel plate and tube is used to provide a robust and durable base. Soft-start rotation prevents unstable loads from toppling when cycle begins.



An optional pallet jack ramp can be mounted in the front or on either side of the Sentry. Also available is a powered walkie ramp with a contour.



Inside the tower, dual ANSI chain and cable track are used for smooth carriage movement. The Sentry uses no-maintenance AC motors with VFD



The film carriage prestretches film 200% prior to wrapping. This reduces material costs and strengthens the film for a tighter and more secure wrap. The machine E-stops if carriage detects an obstacle.

©2018 ProMach Inc. ProMach reserves the right to change or discontinue specifications and designs shown in this brochure without notice or recourse SentryByOrion2018 0917