

FoxJet LS6000 & LS4600 Label Printer Applicator Specifications

| | LS6000 | LS4600 |
|------------------------------|--|--|
| Print Method | Thermal Transfer or Direct Thermal | Thermal Transfer or Direct Thermal |
| Print Engine | SATO, Zebra, Datamax | SATO, Lt408 |
| Print Speed | Up to 16" per second | 6" per second |
| Max Application Speed | 120 PPM / 300 FPM | 300 FPM |
| Print Resolution | 203/300/400/600 dpi | 203 dpi |
| Max Print Area | 6.6" W x 14" L | 4" W x 13" L |
| Min Label Dimensions | 1" W x 0.5" L | 1" W x 1" L |
| Max Label Dimensions | 6.6" W x 14" L | 4" W x 13" L |
| Supply Roll Capacity | 14" (356 mm) OD on 3" (75mm) core, (16" optional) | 14" (356 mm) OD on 3" (75mm) core |
| Max Ribbon Length | 1970' (600m) | 1476' (450m) |
| Power Requirements | 100-240 VAC, 47-63 Hz, 3-6A Auto-ranging | 100-240 VAC, 47-63 Hz, 3-6A Auto-ranging |
| Environmental | 41-104° F (5-40° C); 15-85% RH Non-condensing | 41-104° F (5-40° C); 15-85% RH Non-condensing |
| Dimensions | 31" (787 mm) W x 26" (660 mm) D x 27" (686 mm) H | 31" (787 mm) W x 26" (660 mm) D x 27" (686 mm) H |
| Weight | 120 lbs. applicator, printer, yoke, no stand | 120 lbs. applicator, printer, yoke, no stand |
| Certifications | CE, CSA, ETL (UL 60950), Complies with FCC, part 15 Class A | CE, CSA, ETL (UL 60950), Complies with FCC, part 15 Class A |
| Available Applicator Modules | Wipe Around Side Apply - Heavy Duty; Front, Side, Rear (Two adjacent panels) | Wipe Around Side Apply - Heavy Duty; Front, Side, Rear (Two adjacent panels) |