

Leibinger Jet3 Up Specifications

Power Supply	100-240 V, 50-60 Hz, typical 20 VA
Weight	3.3 lbs printhead, 45.2 lbs cabinet
Dimension	19.13"(W) x 17.55"(H) x 11.25"(D)
Enclosure	Stainless Steel
Environment Protection Rating	IP54 (IP65 optional)
Environment Operating Temperature	41° - 113° F, up to 90% humidity, non-condensing
Printhead Umbilical Length	Flexible umbilical, length: 9.84 ft, optional: 19.68 ft or 32.80 ft
Lines of Print	Multi lines of type (1 to 5 lines)
Print Height	0.06"to 0.63" dependent on nozzle size and head type
Maximum Speed Print	Up to 1960 ft/minute
Auto Codes	Time, auto-adjustable date, auto-adjustable expiration date, weekdays, calendar weeks, Julian calendar, shift identification
Bar Codes	All major barcodes and DataMatrix codes (ECC200), GS1 DataMatrix (EAN/ECC), QR-Code, PPN-Code
Ink Range	Dye-based and Soft Pigmented
Connectivity	Serial interface RS232 up to 115200 baud, USB port, Ethernet (industry standard M12D), script protocol

We service what we sell!

800-727-6566 - www.dvpg.com - info@dvpg.com