

# PSM1412-IC3A

**A low cost solution to your strapping needs.**

The PSM1412-IC3A is designed for general purpose semi automatic strapping. Although it is our lowest priced strapping machine, the low cost does not come at the expense of quality, consistency or reliability. Each PSM1412-IC3A comes with the exclusive PAC machine warranty, including on-line support for the life of the machine. We carry an extensive parts inventory and maintain over 99% parts availability within 24 hours. The PSM1412-IC3A has a convenient operators panel and externally controlled tension. In addition, all electronics are controlled with an integrated circuit control board to minimize down time and maintenance. Pricing on this unit is designed to expand the market to even the occasional user.

## **i** TECHNICAL SPECIFICATIONS

- Dimensions:** 35"L x 23"D x 30"H
- Package Size:** Minimum - 3"W x 1"H  
Maximum - Unlimited
- Weight:** 190lbs.
- Tension Range:** 10 - 100 lbs.
- Speed:** 2.5 seconds per cycle
- Strap Size:** 1/4" - 5/8"
- Core Size:** 8x8  
(additional 9x8 core is available)
- Power Requirements:** 110V, 50/60 Hz



# Impact™ Strapper

**Uniquely designed to out perform traditional semi automatic strappers...**

The impact semi automatic strapper utilizes state-of-the-art technology to give you a machine that is durable, reliable and affordable. The simplistic design of the Impact eliminates chains, belts and pulleys, dramatically reducing repair expenses and costly down time.

## Standard features of the Impact Strapper Include:

- **Electronic Tension Control**  
Consistent, exact tension, with a range of 17 to 100lbs.
- **Adjustable Welding Time**  
Efficient seals, even under extremely high tension.
- **Direct Drive**  
All drive belts, chains and pulleys are eliminated, reducing repair and maintenance costs.
- **24 Volt Power**  
Unparalleled safety.
- **Unique Frame**  
A full size, durable frame, which adjusts to your working height.

*The Impact is also available with the following optional features:*

- A digital readout for tension and feed setting
- A small package option
- A low tension option



## **i** TECHNICAL SPECIFICATIONS

<b>Dimensions:</b>	33.4"L x 22"D x 30.7"H to 37.4"H (adjustable)
<b>Package Size:</b>	Minimum - 3¼"W x 1¼"H 1¾"x1" (with small package option) Maximum - Unlimited
<b>Weight:</b>	155 lbs.
<b>Tension Range:</b>	17 - 100 lbs. 12 - 100 lbs. (with low tension option)
<b>Speed:</b>	2.5 seconds per cycle
<b>Strap Size:</b>	1/4", 5mm - 1/2", 13mm
<b>Core Size:</b>	8x8, 9x8
<b>Power Requirements:</b>	110V, 50/60 Hz