



### **Videojet Unicorn & Unicorn II Inkjet Printer Specifications**

	<b>Unicorn</b>	<b>Unicorn II</b>
Print Height	Standard: 3/8", Optional: 5/16", 1/2", 3/4"	Standard: 1", Optional: 3/4", 1.25", 1.9"
Operating Languages	English, Dutch, Finnish, French, German, Italian, Katakana, Portuguese, Spanish, Swedish; Special Application Units include Arabic, Chinese, Hebrew	English, Dutch Finnish, French, German, Italian, Portuguese, Spanish, Swedish, Norwegian, Turkish, Hungarian
Character Font	7 x 5 dot matrix, 54 printable ASCII characters	7 x 5 dot matrix, 16 x 16 dot matrix
Conveyer Line Speed	20 fpm to 200 fpm	20 fpm to 200 fpm
Message Length	Up to 40 characters	Up to 40 characters of 16 dot font or two 80 character rows of 7 dot font
Message Storage Capacity	Up to 52 messages	Up to 40 messages
Operating Temperature	40°F - 120°F, 4°C - 49°C	40°F - 120°F, 4°C - 49°C
Electrical	System uses universal switching power supply	100 - 240 VAC, 50 - 60 Hz
Ink System	Internally regulated; factor set, no adjustment necessary	Internally regulated; factor set, no adjustment necessary
Ink	8 oz. bladder pressurized, non-aerosol ink bottle; optional 5 gal. bulk w/ ADS required	8 oz. bladder pressurized, non-aerosol ink bottle; optional 5 gal. bulk w/ ADS required
Shipping Weight	14 lbs.	11.45 lbs.

**We service what we sell!**