



FoxJet LS4750 Label Applicator Specifications

	LS4750 Wipe	LS4750 Tamp
Max Application Speed	300 FPM	150 FPM
Min Label Dimensions	1" W x 0.5" L	1" W x 0.5" L
Max Label Dimensions	6" W x 22" L, 9" W x 22" L	6" W x 14" L, 9" x 14" L
Supply Roll Capacity	14" (356 mm) OD	14" (356 mm) OD
Power Requirements	110-240 VAC, 47-63 Hz, 2A Auto-ranging	110-240 VAC, 47-63 Hz, 2A Auto-ranging
Environmental	41-104° F (5-40° C); 15-85% RH Non-condensing	41-104° F (5-40° C); 15-85% RH Non-condensing
Dimensions	31" (787 mm) W x 26" (660 mm) D x 27" (686 mm) H	31" (787 mm) W x 26" (660 mm) D x 27" (686 mm) H
Weight	85 lbs. applicator and yoke, no stand	120 lbs. applicator and yoke, no stand
Certifications	CE, CSA, FCC Approved, Listed (UL60950)	CE, CSA, FCC Approved, Listed (UL60950)
Available Applicator Modules	Wipe Around Side Apply - Heavy Duty; Front, Side, Rear (Two adjacent panels)	Wipe Around Side Apply - Heavy Duty; Front, Side, Rear (Two adjacent panels)

We service what we sell!