

AF-20A

2 mil Aluminum Foil Tape With Acrylic Adhesive & Paper Release Liner

PRODUCT DESCRIPTION

AF-20A is a dead soft high tensile Aluminum Foil coated with an aggressive Acrylic pressure sensitive adhesive carried on a removable paper release liner.

FEATURES/BENEFITS:

This tape is conformable and maximizes adhesive contact to insulation surface. Aggressive adhesive provides quick, positive grab to insulation surface. Malleable foil conforms well to irregular & curved surfaces. Tape performs well at both low and elevated temperatures and can be applied at low temperatures.

APPLICATIONS:

Used for vapor barrier protection, waterproof sealing, heat reflection & dissipation, masking in paint stripping and electroplating.

PHYSICAL PROPERTIES:

Backing	2.0 mil Dead Soft Aluminum
Adhesive	Silicone Adhesive
Total Thickness	1.6 mil Solvent Based Acrylic
Total Thickness (foil+ adhesive)	3.6 mil
Peel Adhesion	73 oz/inch
Tensile Strength	17.1 lbs/inch
Elongation	3.5%
Temperature Range	-22°F to 248°F

SURFACE PREPARATION:

The surface to which the tape is applied should be dry, clean, and free of grease and oil.

STORAGE TEMPERATURE & SHELF LIFE:

Tape should be stored at 70°F/50% relative humidity out of direct sunlight.

Note: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.



**Delaware Valley
Packaging Group**

1425 WELLS DRIVE BENSLEM, PA 19020
STEVE CONWAY (267) 229-2379